

Leica Depthmaster

Depth Indication System



Turn your dipper stick into a measuring tool!

The Leica Depthmaster from Leica Geosystems is designed for Digging applications where only indicate control is required. Mounted on the dipper stick it works with any rotating laser and transforms your dipper stick into a measuring tool. The Leica Depthmaster reception area is 200°. The intensity of the LED cluster of indicator lights can be seen even on the brightest of days and indicates the on grade position relative to the plane of laser light. With its patented internal verticality control system, grade control will be more accurate as verticality is a prerequisite for precise measurements.

KEY BENEFITS

- Works with any rotating laser
- Daily set-up can be done in minutes
- Delivers accurate grade readings with its built-in patented plumb indication
- Can be installed on any excavator or back-hoe
- Comfortable reactivation while in stand-by without leaving the cabin (Shake to Wake)
- Intuitive indications and uses – no extensive studies of manual necessary
- Very easy to understand and use

leica-geosystems.com



- when it has to be **right**

Leica
Geosystems



TECHNICAL DATA	LEICA DEPTHMASTER
Constant Accuracy Band	±1/6" (±4 mm) or ±1/2" (±12 mm)
Sensor Reception Area	8.3" (210 mm) vertical, 200° horizontal
Power Requirements	NiMH, rechargeable battery
Battery Life	Greater than 48 hours of use
Battery Saving	Automatic stand-by after 5 minutes of non-use, complete shut off after 1 1/2 hours
Weight	5.216 lbs. (2,3kg)
Dimension	10 x 5.7 x 3" (254 x 145 x 76 mm)
Clamp-on Brackets Mounting (pipe)	Round 2" (50 mm) Square 1 1/2" (38 mm)
Magnet Mounting	Any flat ferrous surface
Pulling Force	450 lbs. (220 kg)
Weight	5.3 lbs. (2.4 kg)

Constant Accuracy Band (CAB)

Maintains "on-grade" accuracy regardless of operating distances spot size, or rotating laser type, either ±1/6" (4 mm) or ±1/2" (12 mm) depending on jobsite requirements.

Pole Mount

When used with the optional clamp-on assemblies, the Depthmaster can be pole mounted for use on any machine.

Magnetic Mount

The Depthmaster is extremely convenient with its powerful

magnetic mount. It takes seconds to attach to the machine. No drilling or welding is required.

Memory

When the Depthmaster is out of the range of the laser an LED will blink indicating which way to move the sensor to reacquire the laser.

Shake to Wake

The unique "SHAKE TO WAKE" system turns off non-essential electronics after 5 minutes of non-use. It automatically turns back on when your machine begins to move again.

Indicate or Automatic Control

The Depthmaster can be used as an indicate only system using the highly visible LED's for grading or excavating. Using an optional control panel, the Depthmaster can even be used for full hydraulic blade control.

Patented Plumb Indicator

Monitors the excavator's dipper arm vertically for consistent and accurate grade readings.

Mirror Image Mounting

Front and rear display panel of the Depthmaster are the same for mounting on either side of the machine.



Copyright Leica Geosystems AG, 9435 Heerbrugg, Switzerland. All rights reserved. Printed in Switzerland - 2018. Leica Geosystems AG is part of Hexagon AB. 759416en - 04.18



Leica Rugby
CLA & CLH



Leica Rod Eye
Series



Leica ULTRA

Leica Geosystems AG
Heinrich-Wild-Strasse
9435 Heerbrugg, Switzerland
+41 71 727 31 31

- when it has to be **right**

Leica
Geosystems